(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 13 October 2005 (13.10.2005)

PCT

(10) International Publication Number WO 2005/095092 A1

(51) International Patent Classification⁷: B29 30/26

B29D 30/20,

(21) International Application Number:

PCT/IT2004/000160

(22) International Filing Date: 31 March 2004 (31.03.2004)

(25) Filing Language:

Italian

(26) Publication Language:

English

- (71) Applicant (for all designated States except US): PIRELLI PNEUMATICI S.p.A. [IT/IT]; Viale Sarca, 222, I-20126 Milano (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): LACAGNINA, Claudio [IT/IT]; c/o Pirelli Pneumatici S.p.A., 222, Viale Sarca, I-20126 Milano (IT). BRAGHIERI, Luigi [IT/BR]; c/o Pirelli Pneus S.A., Avenida Giovanni Baptista Pirelli, 871, Santo André-SP (BR).
- (74) Agent: TANSINI, Elio, Fabrizio; c/o Bugnion S.P.A., Viale Lancetti, 17, I-20158 Milano (IT).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR MANUFACTURING TYRES FOR VEHICLE WHEELS



(57) Abstract: In the field of tyre building, underbelt inserts (11) are applied to an expandable support (18) associated with an auxiliary drum (14) on which the belt structure is made, simultaneously with manufacture of a carcass structure (3) on a primary drum (13). Following expansion of the expandable support (18), the underbelt inserts (11) are applied to the belt structure (4) that can be directly made on the support (18) itself in an expanded condition. The belt structure (4) together with the underbelt inserts (11) and a tread band (5) are then transferred onto the carcass structure (3) formed on the primary drum (13), to complete building of the tyre (2) following shaping of the carcass (3) into a toroidal conformation.



